



Connector Codes:**

E (N-female) F (N-male) S (SMA-female) T (SMA-male)

Return Loss (50 Ω) in Passband:

near Fco: 20 dB typical = VSWR 1.23 : 1 max.
at the worst point: 14 dB min. = VSWR 1.5 : 1 max.

Model Number	Passband MHz	Max. Insertion Loss			Reject Attenuation	
		at Fco	at 1.03 x Fco	at 1.1 x Fco	40 dB min. at 0.835 x Fco	60 dB min. from DC to 0.765 x Fco
OHP 150-7	150 to 2000	0.94 dB	0.86 dB	0.71 dB	125 MHz	DC to 115 MHz
OHP 160-7	160 to 2000	0.94 dB	0.86 dB	0.71 dB	134 MHz	DC to 122 MHz
OHP 170-7	170 to 2000	0.94 dB	0.86 dB	0.71 dB	142 MHz	DC to 130 MHz
OHP 185-7	185 to 2000	0.87 dB	0.84 dB	0.66 dB	155 MHz	DC to 142 MHz
OHP 200-7	200 to 2000	0.87 dB	0.84 dB	0.66 dB	167 MHz	DC to 153 MHz
OHP 215-7	215 to 2000	0.87 dB	0.84 dB	0.66 dB	180 MHz	DC to 165 MHz
OHP 230-7	230 to 2000	0.87 dB	0.84 dB	0.66 dB	192 MHz	DC to 176 MHz
OHP 245-7	245 to 2000	0.87 dB	0.84 dB	0.66 dB	205 MHz	DC to 187 MHz
OHP 260-7	260 to 3000	0.87 dB	0.84 dB	0.66 dB	217 MHz	DC to 199 MHz
OHP 275-7	275 to 3000	0.87 dB	0.84 dB	0.66 dB	230 MHz	DC to 210 MHz
OHP 300-7	300 to 3000	0.87 dB	0.84 dB	0.66 dB	251 MHz	DC to 230 MHz
OHP 325-7	325 to 3000	0.87 dB	0.84 dB	0.66 dB	271 MHz	DC to 249 MHz
OHP 350-7	350 to 3000	0.87 dB	0.84 dB	0.66 dB	292 MHz	DC to 268 MHz
OHP 375-7	375 to 3000	0.87 dB	0.84 dB	0.66 dB	313 MHz	DC to 287 MHz
OHP 400-7	400 to 3000	0.87 dB	0.84 dB	0.66 dB	334 MHz	DC to 306 MHz
OHP 425-7	425 to 3000	0.87 dB	0.84 dB	0.66 dB	355 MHz	DC to 325 MHz
OHP 450-7	450 to 3000	0.87 dB	0.84 dB	0.66 dB	376 MHz	DC to 344 MHz
OHP 500-7	500 to 3000	0.98 dB	0.91 dB	0.72 dB	418 MHz	DC to 383 MHz
OHP 550-7	550 to 3000	0.98 dB	0.91 dB	0.72 dB	459 MHz	DC to 421 MHz
OHP 600-7	600 to 3000	0.98 dB	0.91 dB	0.72 dB	501 MHz	DC to 459 MHz
OHP 650-7	650 to 3000	0.98 dB	0.91 dB	0.72 dB	543 MHz	DC to 497 MHz