



Mounting Holes $\varnothing = 2.1$ mm

Return Loss (50 Ω) in Passband:
near Fco: 20 dB typical = VSWR 1.23 : 1 max.
at the worst point: 14 dB min. = VSWR 1.5 : 1 max.

Model Number	Passband DC to Fco	Max. Insertion Loss			Reject Attenuation	
		at Fco	at 0.97 x Fco	at 0.90 x Fco	40 dB min. at 2.0 x Fco =	60 dB min. from 2.7 x Fco to
OLP 30-3	30 MHz	0.50 dB	0.45 dB	0.40 dB	60 MHz	81 to 1000 MHz
OLP 35-3	35 MHz	0.50 dB	0.45 dB	0.40 dB	70 MHz	94.5 to 1000 MHz
OLP 40-3	40 MHz	0.50 dB	0.45 dB	0.40 dB	80 MHz	108 to 1000 MHz
OLP 45-3	45 MHz	0.50 dB	0.45 dB	0.40 dB	90 MHz	122 to 1000 MHz
OLP 50-3	50 MHz	0.40 dB	0.35 dB	0.30 dB	100 MHz	135 to 1000 MHz
OLP 55-3	55 MHz	0.40 dB	0.35 dB	0.30 dB	110 MHz	149 to 1000 MHz
OLP 60-3	60 MHz	0.40 dB	0.35 dB	0.30 dB	120 MHz	162 to 1000 MHz
OLP 65-3	65 MHz	0.40 dB	0.35 dB	0.30 dB	130 MHz	176 to 1000 MHz
OLP 70-3	70 MHz	0.40 dB	0.35 dB	0.30 dB	140 MHz	189 to 1000 MHz
OLP 75-3	75 MHz	0.30 dB	0.28 dB	0.25 dB	150 MHz	203 to 1000 MHz
OLP 80-3	80 MHz	0.30 dB	0.28 dB	0.25 dB	160 MHz	216 to 1000 MHz
OLP 90-3	90 MHz	0.30 dB	0.28 dB	0.25 dB	180 MHz	243 to 1000 MHz
OLP 100-3	100 MHz	0.25 dB	0.23 dB	0.22 dB	200 MHz	270 to 1000 MHz
OLP 110-3	110 MHz	0.25 dB	0.23 dB	0.22 dB	220 MHz	297 to 1000 MHz
OLP 120-3	120 MHz	0.25 dB	0.23 dB	0.22 dB	240 MHz	324 to 1000 MHz
OLP 130-3	130 MHz	0.25 dB	0.23 dB	0.22 dB	260 MHz	351 to 1000 MHz
OLP 140-3	140 MHz	0.25 dB	0.23 dB	0.22 dB	280 MHz	378 to 1000 MHz
OLP 150-3	150 MHz	0.25 dB	0.23 dB	0.22 dB	300 MHz	405 to 1000 MHz
OLP 160-3	160 MHz	0.25 dB	0.23 dB	0.22 dB	320 MHz	432 to 1000 MHz
OLP 170-3	170 MHz	0.25 dB	0.23 dB	0.22 dB	340 MHz	459 to 1000 MHz