



型号	通频带	最大插损			抑制衰减	
		DC to Fco	at Fco	at 0.97 x Fco	at 0.90 x Fco	40 dB min. at 1.1 x Fco =
OLP 185-10	18.5 MHz	1.60 dB	1.30 dB	1.00 dB	204 MHz	21.4 to 1000 MHz
OLP 200-10	20.0 MHz	1.60 dB	1.30 dB	1.00 dB	220 MHz	23.1 to 1000 MHz
OLP 215-10	21.5 MHz	1.60 dB	1.30 dB	1.00 dB	237 MHz	24.8 to 1000 MHz
OLP 230-10	23.0 MHz	1.60 dB	1.30 dB	1.00 dB	253 MHz	26.6 to 1000 MHz
OLP 245-10	24.5 MHz	1.60 dB	1.30 dB	1.00 dB	270 MHz	28.3 to 1000 MHz
OLP 260-10	26.0 MHz	1.40 dB	1.10 dB	0.80 dB	286 MHz	30.0 to 1000 MHz
OLP 275-10	27.5 MHz	1.40 dB	1.10 dB	0.80 dB	303 MHz	31.8 to 1000 MHz
OLP 300-10	30.0 MHz	1.30 dB	1.00 dB	0.80 dB	330 MHz	34.7 to 1000 MHz
OLP 325-10	32.5 MHz	1.30 dB	1.00 dB	0.80 dB	358 MHz	37.5 to 1000 MHz
OLP 350-10	35.0 MHz	1.30 dB	1.00 dB	0.80 dB	385 MHz	40.4 to 1000 MHz
OLP 375-10	37.5 MHz	1.30 dB	1.00 dB	0.80 dB	413 MHz	43.3 to 1000 MHz
OLP 400-10	40.0 MHz	1.30 dB	1.00 dB	0.80 dB	440 MHz	46.2 to 1000 MHz
OLP 425-10	42.5 MHz	1.30 dB	1.00 dB	0.80 dB	468 MHz	49.1 to 1000 MHz
OLP 450-10	45.0 MHz	1.30 dB	1.00 dB	0.80 dB	495 MHz	52.0 to 1000 MHz
OLP 500-10	50.0 MHz	1.30 dB	1.00 dB	0.80 dB	550 MHz	57.8 to 1000 MHz
OLP 550-10	55.0 MHz	1.30 dB	1.00 dB	0.80 dB	605 MHz	63.5 to 1500 MHz
OLP 600-10	60.0 MHz	1.30 dB	1.00 dB	0.80 dB	660 MHz	69.3 to 1500 MHz
OLP 650-10	65.0 MHz	1.30 dB	1.00 dB	0.80 dB	715 MHz	75.1 to 1500 MHz
OLP 700-10	70.0 MHz	1.20 dB	0.90 dB	0.70 dB	770 MHz	80.9 to 1500 MHz
OLP 750-10	75.0 MHz	1.20 dB	0.90 dB	0.70 dB	825 MHz	86.6 to 1500 MHz
OLP 800-10	80.0 MHz	1.20 dB	0.90 dB	0.70 dB	880 MHz	92.4 to 2000 MHz
OLP 900-10	90.0 MHz	1.20 dB	0.90 dB	0.70 dB	990 MHz	104.0 to 2000 MHz